

“Reliable and long-lasting performance”



	Jolly	Jolly Top Finish	New Excalibur	Zeus	Dragon	Thor
Max. flow rate	1,9 l/m	1,9 l/m	2,1 l/m	4 l/m	5 l/m	7, 5 l/m
Engine Power	650 watt	650 watt	0,75 Kw	1, 8 Kw (Mod. Benzina: 4,5 kw)	2, 4 Kw	2, 8 Kw
Maximum Pressure	220 bar	220 bar	220 bar	220 bar	230 bar	230 bar
Voltage	230 VAC - 50 Hz	230 VAC - 50 Hz	230 VAC - 50 Hz	230 VAC - 50 Hz	230 VAC - 50 Hz	230 VAC - 50 Hz
Available Voltages	115 VAC - 60 Hz	115 VAC - 60 Hz	115 VAC - 60 Hz	115 VAC - 60 Hz	115 VAC - 60 Hz	115 VAC - 60 Hz
Dimensions	Frame: 450x460x550 mm Trolley: 580x540x995 mm	Trolley: 580x540x995 mm	Frame: 450x460x550 mm Trolley: 580x540x995 mm	Trolley: 600x700x1000 mm	Trolley: 600x700x1000 mm	Trolley: 700x720x1000 mm
Weight	Frame: 15 Kg Trolley: 16 Kg	Trolley: 28 Kg	Frame: 17 Kg Trolley: 18 Kg	Trolley: 60 Kg	Trolley: 66 Kg (Mod. petrol : 70 Kg)	Trolley: 76 Kg
Spray guns	1 AT 250 Spray gun	1 Mist-less gun L400	1 AT 250 Spray gun	1 AT 250 Spray gun 2 AT 250 Spray guns	1 L91 X Spray gun 2 L91 X Spray guns	1 L91 X Spray gun 2 L91 X Spray guns
Nozzle Size	Up to 0,021”	Up to 0,021”	Up to 0,023”	1 spray gun up to 0,029” 2 spray guns up to 0.017”	1 spray gun up to 0.033” 2 spray guns up to 0.019”	1 spray gun up to 0.051” 2 spray guns up to 0.027”

ATTENTION
Max nozzle sizes are only indicative: there can be variations according to paint viscosity and thickness

Fields of Application	Interiors – Exteriors – Industrial buildings – Industrial constructions - Restorations - Roofs		
Main Materials	<p>Lacquers Water paints Acrylics Undercoat paints Enamels Fixatives Paints Emulsions Impregnants Antirust Primer</p>	<p>Water paints Undercoat paints Enamels Fixatives Paints Emulsions Stucco Fillers Bitumens Intumescent Epoxy resins</p>	<p>Smoothers Levelling plaster Pre-mixed plaster (granulometry 0.0) Stucco Plasters Fillers Intumescent Encapsulants Isolants Waterproofing agents Elastomers Epoxy resins Bitumens</p>